

Meet Allworx® Connect™

The VoIP Communication Platform for the Future

More powerful. More advanced. Allworx Connect, our third-generation family of VoIP communication systems, has good looks and serious specs in one compact package.

Highlights

- ✓ Economical and scalable models.
- ✓ High-speed solid state storage subsystem.
- ✓ Bank-grade HTTPS encryption for access security.
- ✓ Wall- and rack-mountable.
- ✓ Interoperability with the latest VoIP standards used by major carriers.
- ✓ Native Gigabit Ethernet interfaces with VLANs.
- ✓ Models with or without analog FXO ports.







- For up to 180 users.2
- · 60 concurrent external calls.
- Two FXO ports.
- · Two FXS ports.
- Three network ports.
- One T1 port.3



Allworx Connect 536 and 530

- For up to 50 users.2
- 30 concurrent external calls.
- With or without six FXO ports.
- · Two FXS ports.
- Three network ports.



Allworx Connect 324 and 320

- For up to 20 users.2
- 12 concurrent external calls.
- · With or without four FXO ports.
- · Two FXS ports.
- · Two network ports.

Allworx Px 6/2 Expander — Add extra analog ports to any Connect system.



- Six FXO and two FXS ports.
- Up to three units can be added to a Connect 731, 536, and 530.
- One unit can be added to a Connect 324 and 320.

All Connect systems require Allworx System Software 8.0 or higher.

1. As of June 2016. 2. Requires an additional software license key(s) to expand users above the base. 3. Requires an additional software license key

It's easy to grow your business with Allworx Connect.



Not sure how many employees you'll be adding in the future? You can always trade up from one Connect system to another with ease.

Or perhaps you have an older Allworx system (6x12, 6x, 48x, or 24x) you're looking to upgrade? Trade in for a brand new Connect system at a price that's easy on the wallet.



Allworx® Connect™ System Specifications

	731	536	530	324	320
SYSTEM FEATURES					
Maximum Users 1/Base Users	180/30	50/30	50/30	20/12	20/12
Maximum System Extensions ² /Base System Extensions	180/30	50/30	50/30	20/12	20/12
Concurrent External Calls	60	30	30	12	12
Maximum Handsets ³	360	100	100	40	40
FXO Ports	2	6	0	4	0
FXS Ports	2	2	2	2	2
Network Ports	3	3	3	2	2
T1 Port ¹	1	0	0	0	0
Conference Bridges ¹	4	1	1	1	1
Users per Bridge ¹	30	8	8	8	8
Concurrent Users on All Bridges ¹	30	8	8	8	8
Number of Queues ¹	10	10	10	10	10
Calls per Queue ¹	60	30	30	12	12
Concurrent Calls in All Queues ¹	60	30	30	12	12
Voicemail Ports	15	8	8	4	4
Auto Attendants ⁴	32	16	16	9	9
Auto Attendant Ports	16	8	8	4	4
Presence Settings	7	7	7	7	7
VoIP with Integrated SIP 2.0	Included	Included	Included	Included	Included
Voicemail-to-Email	Included	Included	Included	Included	Included
Customized Call Routes with Unlimited Options	Included	Included	Included	Included	Included
Plug-N-Play Remote IP Phone Support	Included	Included	Included	Included	Included
10 Customizable Paging Zones	Included	Included	Included	Included	Included
Door Relay ⁵	Included	Included	Included	Included	Included
Secure (HTTPS) Web Administration	Included	Included	Included	Included	Included
My Allworx Manager for End-Users	Included	Included	Included	Included	Included
Basic Call Detail Reports	Included	Included	Included	Included	Included
TSP (TAPI) Driver	Included	Included	Included	Included	Included
SIP Video Support	Included	Included	Included	Included	Included
Allworx OfficeSafe™ for Data Backup	Included	Included	Included	Included	Included
Native Gigabit Ethernet Interfaces with VLANs	Included	Included	Included	Included	Included
Integrated SPI Firewall, NAT, and Routing Capability	Included	Included	Included	Included	Included
SUPPORTED ADVANCED SOFTWARE OPTIONS ¹	meidaea	meladea	meladea	meiadea	moidaca
Allworx Advanced Multi-Site Primary ¹	•	•	•	•	•
Allworx Advanced Multi-Site Branch ¹	•	•	•	•	•
Allworx Call Queuing ¹	•	•	•	•	•
Allworx Automatic Call Distribution (ACD) ¹	•	•	•		
Allworx View™1	•	•	•	•	•
Allworx View ACD ¹	•	•	•		-
Allworx Conference Center ¹	•	•	•	•	•
	•	•	•	•	•
Allworx Dual Language Support ¹ Allworx Mobile VM ^{1,6}	•	•	•	•	•
			-	•	•
Allwary Basah Lipk™1	•	•	•		•
Allworx Reach Link™¹	•	•	•	•	•
Allworx Interact™ Professional 1	•	•	•	•	•
Allworx Interact Sync™1	•	•	•	•	•
Generic SIP Device Registration ¹	•	•	•	•	•

Requires an additional advanced software license key(s).
 A system extension does not have an individual voicemail box (e.g., break room, customer service queue). The
maximum number of system extensions is equal to the maximum number of user licenses available for a server.
 Handsets include Allworx IP phones, activated Allworx Reach licenses, generic SIP devices, and analog devices.

Requires Allworx System Software 8.1 or higher.
 Requires a third-party electronic door lock device (not included).
 Called Mobile Link prior to Allworx System Software 8.0.